



SOA1550

INTRODUCTION

- ◆ Single/dual input for choice, built in optical switch for dual input, the switching power can be set by the button in the front panel or by web SNMP.
- ◆ Output adjustable by buttons in the front panel or web SNMP, the range is down 4dBm
- ◆ Maintenance function of one-time downward attenuation of 6dBm by buttons in the front panel or web SNMP, to facilitate the optical fiber hot-plug operation without turn off the device
- ◆ Standard RJ 45 port for remote control, we can provide output contract and web manager for choice, and also plug-in SNMP hardware can be reserved for update.
- ◆ With laser key to turn on/off the laser.
- ◆ With RF test function.
- ◆ Adopts JDSU or Oclaro Pump laser
- ◆ Led displays the working condition of the machine
- ◆ Dual power hot plug power supply for choice, 90V~250V AC or -48V DC

Items	parameter									
Output (dBm)	31	32	33	34	35	36	37	38	39	40
Output (mW)	1250	1600	2000	2500	3200	4000	5000	6400	8000	10000
Input(dBm)	-8~+10									
Range of output adjustment (dBm)	Down 4									
one-time downward attenuation(dBm)	Down 6									
Wavelength (nm)	1540~1565									
Output stability(dB)	<±0.3									
Optical Return Loss (dB)	≥45									
Fiber Connector	FC/APC、SC/APC、SC/IUPC、LC/APC、LC/UPC									
Noise Figure (dB)	<6.0(input 0dBm)									
Web port	RJ45(SNMP)									
Power Consumption (W)	≤80									
Voltage (V)	220VAC(90~265)、-48VDC									
Working Temp (℃)	-0~55									
Size (mm)	370(L)×486(W)×45(H)									
NW (Kg)	8									

SOFTEL

HANGZHOU SOFTEL OPTIC CO.,LTD